

Big Tent 12M



Clear-span width

1200 cm

Side height

300 cm

Ridge height

520 cm

Roof pitch

20°

Bay distance

500 cm

Gable uprights

2 gable uprights (per end)

Longest component

660 cm

Minimum tent length

1000 cm

Maximum tent length

No limit

Main profile

160 mm x 100 mm x 3 mm

Eave / corner connection

Slide connection

Max. allowed wind speed to DIN

100 km/h

Wind Load

0.5 kN/m²

Extension / lean-to options

Extension (max. span 300 cm and 4 bays, located anywhere, not both sides)

Flooring options

Woodenfloor with timber or steel sub-construction

Aluminium cassettefloor with plywood or full aluminiumboards




Compactfloor

Cover

RÖDER No. 1: PVC-coated polyester textile, flame retardant to DIN 4102 B1, M2

Special design

By using compactfloor anchoring can be omitted



17.05.2012, www.r-zs.de/en/tents/pdf/180

RÖDER Zelt- und Veranstaltungsservice GmbH
63654 Büdingen Fon: +49 06049 700-0
Verkauf: Am Lautenstein Fax: +49 06049 700-339
Vermietung: An den Ellern Fon: +49 06049 700-309
HRB 3261, Friedberg UST.-IdNr.: DE 112607812

Geschäftsführer:
Rüdiger Blasius
Jens Brüggemann
Thomas Roman
St.-Nr.: 020 225 62014

Bank:
WGZ Bank eG
KBC Bank DTLD AG
Duns-Nr.: 32-239-9494

IBAN BLZ Konto
DE73 400 600 00 0000 772 633
DE86 500 203 00 0000 295 086

SWIFT/BIC
GENO DE MS
BANV DE HB 500

info@r-zs.com www.r-zs.com