

Big Tent 15M



Clear-span width

1500 cm

Side height

400 cm

Ridge height

640 cm

Roof pitch

18°

Bay distance

500 cm

Gable uprights

2 gable uprights (per end)

Longest component

800 cm

Minimum tent length

1000 cm

Maximum tent length

No limit

Eave / corner connection

Twin-pin connection with corner strut

Max. allowed wind speed to DIN

100 km/h

Wind Load

0.5 kN/m²

Extension / lean-to options

Extension (max. span 500 cm located anywhere, both sides, any length)

Flooring options

Woodenfloor with timber and steel sub-construction




Aluminium cassettefloor with plywood or full aluminiumboards

Cover

RÖDER No. 1: PVC-coated polyester textile, flame retardant to DIN 4102 B1, M2

Special design

Portal beams can be used in place of cross struts



17.05.2012, www.r-zs.de/en/tents/pdf/58

RÖDER Zelt- und Veranstaltungsservice GmbH
 63654 Büdingen Fon: +49 06049 700-0
 Verkauf: Am Lautenstein Fax: +49 06049 700-339
 Vermietung: An den Ellern Fon: +49 06049 700-309
 HRB 3261, Friedberg UST-IdNr.: DE 112607812

Geschäftsführer:
 Rüdiger Blasius
 Jens Brüggemann
 Thomas Roman
 St.-Nr.: 020 225 62014

Bank:
 WGZ Bank eG
 KBC Bank DTLD AG
 Duns-Nr.: 32-239-9494

IBAN BLZ Konto
 DE73 400 600 00 0000 772 633
 DE86 500 203 00 0000 295 086
 info@r-zs.com

SWIFT/BIC
 GENO DE MS
 BANV DE HB 500
 www.r-zs.com