

# Big Tent 30M



## Clear-span width

3000 cm

## Side height

300 cm

## Ridge height

787 cm

## Roof pitch

18°

## Bay distance

500 cm

## Gable uprights

5 gable uprights (per end)

## Longest component

1070 cm

## Minimum tent length

2000 cm

## Maximum tent length

No limit

## Main profile

250 mm x 120 mm x 5/4 mm

## Eave / corner connection

Clevic-plate connection with ridge strut

## Max. allowed wind speed to DIN

100 km/h

## Wind Load

0.5 kN/m<sup>2</sup>

## Extension / lean-to options

Extension (max. span 500 cm, located anywhere, both sides, any length)

1/2 dodecagonal at gable end

## Flooring options

Woodenfloor with timber and steel sub-construction




Aluminium cassettefloor with plywood or full aluminiumboards

## Cover

RÖDER No. 1: PVC-coated polyester textile, flame retardant to DIN 4102 B1, M2

## Special design

Portal beams can be used in place of cross struts



17.05.2012, [www.r-zs.de/en/tents/pdf/72](http://www.r-zs.de/en/tents/pdf/72)

RÖDER Zelt- und Veranstaltungsservice GmbH  
63654 Büdingen  
Verkauf: Am Lautenstein  
Vermietung: An den Ellern  
HRB 3261, Friedberg  
Fon: +49 06049 700-0  
Fax: +49 06049 700-339  
Fon: +49 06049 700-309  
UST.-IdNr.: DE 112607812

Geschäftsführer:  
Rüdiger Blasius  
Jens Brüggemann  
Thomas Roman  
St.-Nr.: 020 225 62014

Bank:  
WGZ Bank eG  
KBC Bank DTLD AG  
Duns-Nr.: 32-239-9494

IBAN BLZ Konto  
DE73 400 600 00 0000 772 633  
DE86 500 203 00 0000 295 086  
info@r-zs.com

SWIFT/BIC  
GENO DE MS  
BANV DE HB 500  
www.r-zs.com