

Storage Tent S75-Alu 17,5M



Clear-span width

1750 cm

Side height

440 cm

Ridge height

686 cm

Roof pitch

15°

Bay distance

250 cm

Gable uprights

4 gable uprights (per end)

Longest component

917 cm

Minimum tent length

1500 cm

Maximum tent length

No limit

Main profile

220 mm x 100 mm x 4 mm

Door sizes (PVC door panels)

Side wall 220 cm x 390 cm

Gable end 450 cm x 430 cm

Eave / corner connection

Internal eave insert

Max. allowed wind speed to DIN

100 km/h

Wind Load

0.5 kN/m²

Snow load

0.75 kN/m²




Cover

RÖDER No. 1: PVC-coated polyester textile,
flame retardant to DIN 4102 B1, M2

Special design

Sliding doors, rolling doors or service entrances

Trapezoidal metal sheets



22.05.2012, www.r-zs.de/en/tents/pdf/188

RÖDER Zelt- und Veranstaltungsservice GmbH
63654 Büdingen Fon: +49 06049 700-0
Verkauf: Am Lautenstein Fax: +49 06049 700-339
Vermietung: An den Ellern Fon: +49 06049 700-309
HRB 3261, Friedberg UST.-IdNr.: DE 112607812

Geschäftsführer:
Rüdiger Blasius
Jens Brüggemann
Thomas Roman
St.-Nr.: 020 225 62014

Bank:
WGZ Bank eG
KBC Bank DTLD AG
Duns-Nr.: 32-239-9494

IBAN BLZ Konto
DE73 400 600 00 0000 772 633
DE86 500 203 00 0000 295 086
info@r-zs.com

SWIFT/BIC
GENO DE MS
BANV DE HB 500
www.r-zs.com