

# Storage Tent S75-Alu 5M



**Clear-span width**

500 cm

**Side height**

500 cm

**Ridge height**

576 cm

**Roof pitch**

15°

**Bay distance**

250 cm

**Gable uprights**

2 gable uprights (per end)

**Longest component**

515 cm

**Minimum tent length**

750 cm

**Maximum tent length**

No limit

**Main profile**

170 mm x 88 mm x 3 mm

**Door sizes (PVC door panels)**

Side wall 220 cm / 450 cm x 450 cm

Gable end 220 cm x 430 cm

**Eave / corner connection**

Internal eave insert

**Max. allowed wind speed to DIN**

100 km/h

**Wind Load**

0.5 kN/m<sup>2</sup>

**Snow load**

0.25 kN/m<sup>2</sup>



**Cover**

RÖDER No. 1: PVC-coated polyester textile, flame retardant to DIN 4102 B1, M2

**Special design**

Movable system on rollers, also available in fold-up version

Trapezoidal metal sheets



22.05.2012, [www.r-zs.de/en/tents/pdf/183](http://www.r-zs.de/en/tents/pdf/183)

RÖDER Zelt- und Veranstaltungsservice GmbH  
 63654 Büdingen Fon: +49 06049 700-0  
 Verkauf: Am Lautenstein Fax: +49 06049 700-339  
 Vermietung: An den Ellern Fon: +49 06049 700-309  
 HRB 3261, Friedberg UST-IdNr.: DE 112607812

Geschäftsführer:  
 Rüdiger Blasius  
 Jens Brüggemann  
 Thomas Roman  
 St.-Nr.: 020 225 62014

Bank:  
 WGZ Bank eG  
 KBC Bank DTLD AG  
 Duns-Nr.: 32-239-9494

IBAN BLZ Konto  
 DE73 400 600 00 0000 772 633  
 DE86 500 203 00 0000 295 086

SWIFT/BIC  
 GENO DE MS  
 BANV DE HB 500  
 info@r-zs.com www.r-zs.com