

Storage Tent S75-Alu 7,5M



Clear-span width

750 cm

Side height

500 cm

Ridge height

610 cm

Roof pitch

15°

Bay distance

250 cm

Gable uprights

2 gable uprights (per end)

Longest component

551 cm

Minimum tent length

750 cm

Maximum tent length

No limit

Main profile

170 mm x 88 mm x 3 mm

Door sizes (PVC door panels)

Side wall 220 cm / 450 cm x 450 cm

Gable end 310 cm x 430 cm

Eave / corner connection

Internal eave insert

Max. allowed wind speed to DIN

100 km/h

Wind Load

0.5 kN/m²

Snow load

0.25 kN/m²



Cover

RÖDER No. 1: PVC-coated polyester textile, flame retardant to DIN 4102 B1, M2

Special design

Movable system on rollers, also available in fold-up version

Trapezoidal metal sheets



22.05.2012, www.r-zs.de/en/tents/pdf/184

RÖDER Zelt- und Veranstaltungsservice GmbH
63654 Büdingen
Fon: +49 06049 700-0
Fax: +49 06049 700-339
An den Ellern
HRB 3261, Friedberg
Fon: +49 06049 700-309
UST-IdNr.: DE 112607812

Geschäftsführer:
Rüdiger Blasius
Jens Brüggemann
Thomas Roman
St.-Nr.: 020 225 62014

Bank:
WGZ Bank eG
KBC Bank DTLD AG
Duns-Nr.: 32-239-9494

IBAN BLZ Konto
DE73 400 600 00 0000 772 633
DE86 500 203 00 0000 295 086

SWIFT/BIC
GENO DE MS
BANV DE HB 500
info@r-zs.com
www.r-zs.com